




SMA Coaxial Fixed Attenuator, R12S50U-XX DC-12.4GHz, 50W, 1-40dB, Unidirectional, Round

Dimensions(mm) Tolerance±1%



Electrical & Environmental

Frequency Range	DC-12.4GHz , 50Ohms
VSWR	1.35 Max
Input Avg Power	50W @25°C
Peak Power	500W (5μsec pulse width, 5% duty cycle)
Temp Coefficient	<0.0004 dB/dB/°C
Direction	Unidirectional, SMA female input to SMA female output
Attenuation	1-40dB
Operating Temp	-55°C~+100°C

Product Selection, Customizable


RFTOP P/N	Values	Accuracy
R12S50U-3	3dB	±0.6dB
R12S50U-6	6dB	±0.6dB
R12S50U-10	10dB	±0.6dB
R12S50U-20	20dB	±0.7dB
R12S50U-30	30dB	±0.8dB
R12S50U-40	40dB	±1.0dB

Notes: Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 5W at 100°C.

Mechanical & Product Information

Product Number	R12S50U-XX
Product Type	Coaxial Fixed Attenuator, P-Grade
Connector	SMA female, SMA female
Connector Body	Ternary alloy plated brass
Center Contact	Gold plated brass, Gold plated beryllium copper
Heat Sink	Black anodized aluminum
Net Weight	About 170.0g

1. Customized connectors, dimensions, directionality, PIM, dB values.
2. Refer to the RFTOP attenuator selection and usage guide.





SMA Coaxial Fixed Attenuator, R12S50U-XX DC-12.4GHz, 50W, 1-40dB, Unidirectional, Round

Typical Test Data

