




N Coaxial Fixed Attenuator, R18N200UA-XX DC-18GHz, 200W, 10-60dB, Unidirectional, Rectangular

Dimensions(mm) Tolerance $\pm 1\%$



Electrical & Environmental

Frequency Range	DC-18GHz , 50Ohms
VSWR	1.45 Max
Input Avg Power	200W @25°C
Peak Power	1kW (5μsec pulse width, 10% duty cycle)
Temp Coefficient	<0.0004 dB/dB/°C
Direction	Unidirectional, N male input to N female output
Attenuation	10-60dB
Operating Temp	-55°C~+100°C


Product Selection, Customizable

RFTOP P/N	Values	Accuracy
R18N200UA-6	6dB	± 2.5 dB
R18N200UA-10	10dB	± 2.5 dB
R18N200UA-20	20dB	± 2.0 dB
R18N200UA-30	30dB	± 1.5 dB
R18N200UA-40	40dB	± 1.3 dB
R18N200UA-50	50dB	± 1.4 dB
R18N200UA-60	60dB	± 1.4 dB

Mechanical & Product Information

Product Number	R18N200UA-XX
Product Type	Coaxial Fixed Attenuator, P-Grade
Connector	N male, N female
Connector Body	Passivated stainless steel
Center Contact	Gold plated brass, Gold plated beryllium copper
Heat Sink	Black anodized aluminum
Net Weight	About 3.0kg

Notes: Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 20W at 100°C.



1. Customized connectors, dimensions, directionality, PIM, dB values.
2. Refer to the RFTOP attenuator selection and usage guide.



N Coaxial Fixed Attenuator, **R18N200UA-XX** DC-18GHz, 200W, 10-60dB, Unidirectional, Rectangular

Typical Test Data

