


## BNC Coaxial Fixed Attenuator, R3B50UA-XX DC-3GHz, 50W, 1-60dB, Unidirectional, Rectangular

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	DC-3GHz , 50Ohms
<b>VSWR</b>	1.2 Max
<b>Input Avg Power</b>	50W @25°C
<b>Peak Power</b>	500W (5μsec pulse width, 3% duty cycle)
<b>Temp Coefficient</b>	<0.0004 dB/dB/°C
<b>Direction</b>	Unidirectional, BNC male input to BNC female output
<b>Attenuation</b>	1-60dB
<b>Operating Temp</b>	-55°C~+125°C

### Product Selection, Customizable

RFTOP P/N	ATTEN	Accuracy
R3B50UA-3	3 dB	±0.4 dB
R3B50UA-6	6 dB	±0.4 dB
R3B50UA-10	10 dB	±0.4 dB
R3B50UA-20	20 dB	±0.5 dB
R3B50UA-30	30 dB	±0.7 dB
R3B50UA-40	40 dB	±0.8 dB
R3B50UA-50	50 dB	±0.8 dB
R3B50UA-60	60 dB	±0.9 dB

### Mechanical & Product Information

<b>Product Number</b>	R3B50UA-XX
<b>Product Type</b>	Coaxial Fixed Attenuator, P-Grade
<b>Connector</b>	BNC male, BNC female
<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated brass, Gold plated beryllium copper
<b>Heat Sink</b>	Black anodized aluminum

1. Customized connectors, dimensions, directionality, PIM, dB values.
2. Refer to the RFTOP attenuator selection and usage guide.

**Notes:** Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 5W at 100°C.

