


2.92mm(K,SK) Coaxial Fixed Attenuator, R4010X-XX DC-40GHz, 10W, 1-30dB, Bidirectional, Round

Dimensions(mm) Tolerance $\pm 1\%$



Electrical & Environmental

Frequency Range	DC-40GHz , 50Ohms
VSWR	1.25 Max
Input Avg Power	10W @25°C
Peak Power	100W (5μsec pulse width, 5% duty cycle)
Temp Coefficient	<0.0004 dB/dB/°C
Direction	Bidirectional, 2.92mm male to 2.92mm female
Attenuation	1-30dB
Operating Temp	-55°C~+125°C

Product Selection, Customizable

RFTOP P/N	ATTEN	Accuracy
R4010X-3	3 dB	+1.0/-0.6 dB
R4010X-6	6 dB	+1.0/-0.6 dB
R4010X-10	10 dB	+1.0/-0.6 dB
R4010X-20	20 dB	+1.0/-0.8 dB
R4010X-30	30 dB	+1.0/-0.8 dB

Notes: Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 60°C. Reference Curve, derate linearly to 1W at 100°C.

Mechanical & Product Information

Product Number	R4010X-XX
Product Type	Coaxial Fixed Attenuator, P-Grade
Connector	2.92mm(K,SK) male, 2.92mm(K,SK) female
Connector Body	Passivated stainless steel
Center Contact	1.27μm Gold plated brass & beryllium copper
Heat Sink	Black anodized aluminum
Net Weight	About 34.0g

1. Customized connectors, dimensions, directionality, PIM, dB values.
2. Refer to the RFTOP attenuator selection and usage guide.

Power derating Versus temperature

