




2.92mm Coaxial Fixed Attenuator, R4045U-XX DC-40GHz, 45W, 10-40dB, Unidirectional, Round

Dimensions(mm) Tolerance±1%



Electrical & Environmental

Frequency Range	DC-40GHz , 50Ohms
VSWR	1.38 Max
Input Avg Power	45W @25°C
Peak Power	200W (5μsec pulse width, 10% duty cycle)
Temp Coefficient	<0.0004 dB/dB/°C
Direction	Unidirectional, 2.92mm male input to 2.92mm female output
Attenuation	10-40dB
Operating Temp	-55°C~+100°C

Product Selection, Customizable


RFTOP P/N	Values	Accuracy
R4045U-10	10dB	+3.2/-2.8dB
R4045U-20	20dB	+2.5/-2.2dB
R4045U-30	30dB	±2.2dB
R4045U-40	40dB	±2.2dB

Notes: Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 5W at 100°C.

Mechanical & Product Information

Product Number	R4045U-XX
Product Type	Coaxial Fixed Attenuator, JP-Grade
Connector	2.92mm male, 2.92mm female
Connector Body	Passivated stainless steel
Center Contact	1.27um Gold plated beryllium copper
Heat Sink	Black anodized aluminum
Net Weight	About 180.0g

Power derating Versus temperature



1. Customized connectors, dimensions, directionality, PIM, dB values.

2. Refer to the RFTOP attenuator selection and usage guide.