




N Coaxial Fixed Attenuator, R4N150UB-XX DC-4GHz, 150W, 3-60dB, Unidirectional, Rectangular

Dimensions(mm) Tolerance±1%



Electrical & Environmental

Frequency Range	DC-4GHz , 50Ohms
VSWR	1.2 Max
Input Avg Power	150W @25°C
Peak Power	1kW (5μsec pulse width, 5% duty cycle)
Temp Coefficient	<0.0004 dB/dB/°C
Direction	Unidirectional, N male input to N female output
Attenuation	3-60dB
Operating Temp	-55°C~+100°C


Product Selection, Customizable

RFTOP P/N	Values	Accuracy
R4N150UB-6	6dB	±0.7dB
R4N150UB-10	10dB	±0.7dB
R4N150UB-20	20dB	±0.7dB
R4N150UB-30	30dB	±0.8dB
R4N150UB-40	40dB	±0.9dB
R4N150UB-50	50dB	±0.9dB
R4N150UB-60	60dB	±0.9dB

Mechanical & Product Information

Product Number	R4N150UB-XX
Product Type	Coaxial Fixed Attenuator, P-Grade, Miniature Size
Connector	N male, N female
Connector Body	Ternary alloy plated brass
Center Contact	Gold plated brass, Gold plated beryllium copper
Heat Sink	Black anodized aluminum
Net Weight	About 1,000.0g

Notes: Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 15W at 100°C.



1. Customized connectors, dimensions, directionality, PIM, dB values.

2. Refer to the RFTOP attenuator selection and usage guide.