


## N Coaxial Fixed Attenuator, R4N25FF-XX DC-4GHz, 25W, 1-60dB, Bidirectional, Round

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	DC-4GHz , 50Ohms
<b>VSWR</b>	1.2 Max
<b>Input Avg Power</b>	25W @25°C
<b>Peak Power</b>	800W (5μsec pulse width, 1.5% duty cycle)
<b>Temp Coefficient</b>	<0.0004 dB/dB/°C
<b>Direction</b>	Bidirectional, N female to N female
<b>Attenuation</b>	1-60dB
<b>Operating Temp</b>	-55°C~+125°C


### Product Selection, Customizable

RFTOP P/N	ATTEN	Accuracy
R4N25FF-3	3 dB	±0.4 dB
R4N25FF-6	6 dB	±0.4 dB
R4N25FF-10	10 dB	±0.4 dB
R4N25FF-20	20 dB	±0.5 dB
R4N25FF-30	30 dB	±0.6 dB
R4N25FF-40	40 dB	±0.7 dB
R4N25FF-50	50 dB	±0.8 dB
R4N25FF-60	60 dB	±0.9 dB

### Mechanical & Product Information

<b>Product Number</b>	R4N25FF-XX
<b>Product Type</b>	Coaxial Fixed Attenuator, P-Grade
<b>Connector</b>	N female, N female
<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated beryllium copper
<b>Heat Sink</b>	Black anodized aluminum
<b>Net Weight</b>	About 135.0g

**Notes:** Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 3W at 100°C.



1. Customized connectors, dimensions, directionality, PIM, dB values.

2. Refer to the RFTOP attenuator selection and usage guide.