




## SMA Coaxial Fixed Attenuator, R6S50UA-XX DC-6GHz, 50W, 1-50dB, Unidirectional, Rectangular

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental


<b>Frequency Range</b>	DC-6GHz , 50Ohms
<b>VSWR</b>	1.25 Max
<b>Input Avg Power</b>	50W @25°C
<b>Peak Power</b>	500W (5μsec pulse width, 5% duty cycle)
<b>Temp Coefficient</b>	<0.0004 dB/dB/°C
<b>Direction</b>	Unidirectional, SMA male input to SMA female output
<b>Attenuation</b>	1-50dB
<b>Operating Temp</b>	-55°C~+100°C

Product Selection, Customizable		
RFTOP P/N	Values	Accuracy
R6S50UA-3	3dB	±0.5dB
R6S50UA-6	6dB	±0.5dB
R6S50UA-10	10dB	±0.5dB
R6S50UA-20	20dB	±0.6dB
R6S50UA-30	30dB	±0.8dB
R6S50UA-40	40dB	±0.8dB
R6S50UA-50	50dB	±0.8dB

### Mechanical & Product Information

<b>Product Number</b>	R6S50UA-XX
<b>Product Type</b>	Coaxial Fixed Attenuator, P-Grade
<b>Connector</b>	SMA male, SMA female
<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated brass, Gold plated beryllium copper
<b>Heat Sink</b>	Black anodized aluminum
<b>Net Weight</b>	About 1.1kg

**Notes:** Pay attention to input/output. To ensure longevity and performance, do not use at full power for a long time. Peak power, pulse width, and duty cycle need to meet the requirements. Input high power, require heat dissipation, maintain temperature within 80°C. Reference Curve, derate linearly to 5W at 100°C.



1. Customized connectors, dimensions, directionality, PIM, dB values.

2. Refer to the RFTOP attenuator selection and usage guide.