


Armored Test Cable Assembly, RCP600-NMNF-L N Male to N Female, DC-18GHz, ø6mm

Dimensions(mm) Tolerance±1%



Electrical & Environmental


Frequency Range	DC-18GHz, 50 Ohms
Avg Power@25°C	114W @18GHz, 203W @6GHz
Insertion Loss@1M	2.3 dB Max @18GHz
VSWR	1.2 Max
Velocity of Propagation	76%
Shielding Effectiveness	90dB Min
Attenuation stability	±0.05dB Max
Withstand Voltage	500V@DC
Mechanical Phase	±7°
OT	-55~+165°C

Product Information

Product Number	RCP600-NMNF-L
Product Type	Armored Test Cable Assembly
Cable	RCT360/RCP600
Connector	N Male to N Female
Connector Body	Passivated stainless steel
Center Contact	Gold plated beryllium copper
Bend Radius	18.00mm
Bend Radius (Repeated)	36.00mm

Customized services: including connectors, length, phase matching/tracking, time delay, and better electrical performance.

RCT360/RCP600 Structure Characteristics



Structure	Material	ΦD(mm)
1.Center Conductor	Single-core Silver-plated Copper	0.72
2.Dielectric	LD-PTFE	2.10
3.Inner shield	Silver-plated Copper Tape Wrapping	2.25
4.Interlayer	LD-PTFE	2.55
5.Outer Shield	Silver-plated Copper Wire Braiding	3.01
6.Jacket	Blue FEP	3.60
7.Spring	Stainless steel Tape	4.95
8.Braided Layer	Tin-plated Copper Wire	5.20
9.Stable Layer	PTFE	5.50
10.Armor Jacket	Purplish Black PTFE	6.00

Product Selection and Loss Index @25°C

RFTOP P/N	3GHz	10GHz	18GHz
RCP600-NMNF-600	0.7 dB	1.15 dB	1.46 dB
RCP600-NMNF-1M	1.04 dB	1.79 dB	2.3 dB
RCP600-NMNF-1.5M	1.46 dB	2.59 dB	3.35 dB
RCP600-NMNF-2M	1.88 dB	3.38 dB	4.4 dB