


Armored Test Cable Assembly, RCP600H-UFUF-L 2.4mm Female to 2.4mm Female, DC-50GHz, ø6mm

Dimensions(mm) Tolerance $\pm 1\%$



Electrical & Environmental


Frequency Range	DC-50GHz, 50 Ohms
Avg Power@25°C	47.6W @50GHz
I L@1M	4.19 dB Max @50GHz
VSWR	1.3 Max
VOP	76%
SE	90dB Min
ATTEN-STAB	± 0.08 dB Max
Mech. Phase	$\pm 6.7^\circ$
OT	-40~+150°C

Product Information

Product Number	RCP600H-UFUF-L
Product Type	Armored Test Cable Assembly
Cable	RCT360Z/RCP600
Connector	2.4mm Female to 2.4mm Female
Connector Body	Passivated stainless steel
Center Contact	Gold plated beryllium copper
Bend Radius	24.00mm
Bend Radius (Rep.)	48.00mm

Customized services: including connectors, length, phase matching/tracking, time delay, and better electrical performance.

RCT360Z/RCP600 Structure Characteristics



Structure	Material	ΦD(mm)
1.Center Conductor	Single-core Silver-plated Copper	0.72
2.Dielectric	LD-PTFE	2.10
3.Inner shield	Silver-plated Copper Tape Braiding	2.25
4.Interlayer	LD-PTFE	2.55
5.Outer Shield	Silver-plated Copper Wire Braiding	3.01
6.Jacket	Yellow FEP	3.60
7.Spring	Stainless steel Tape	4.95
8.Braided Layer	Tinned Wire	5.20
9.Stable Layer	PTFE	5.50
10.Armor Jacket	Purplish Black PTFE	6.00

Product Selection and Loss Index @25°C

RFTOP P/N	3GHz	26GHz	50GHz
RCP600H-UFUF-600	1.10 dB	2.14 dB	2.75 dB
RCP600H-UFUF-1M	1.44 dB	3.17 dB	4.19 dB
RCP600H-UFUF-1.5M	1.86 dB	4.46 dB	5.99 dB
RCP600H-UFUF-2M	2.28 dB	5.74 dB	7.78 dB