


Armored Test Cable Assembly, RCP760H-NMNM-L N Male to N Male, DC-18GHz, Ø7.6mm

Dimensions(mm) Tolerance±1%



Electrical & Environmental

Frequency Range	DC-18GHz, 50 Ohms
Avg Power@25°C	84W @18GHz
IL@1M	1.88 dB Max @18GHz
VSWR	1.25 Max
VOP	76%
SE	90dB Min
ATTEN-STAB	±0.03dB Max
Mech. Phase	±2.7°
OT	-40~+150°C

Product Information

Product Number	RCP760H-NMNM-L
Product Type	Armored Test Cable Assembly
Cable	RCT500/RCP760
Connector	N Male to N Male
Connector Body	Passivated stainless steel
Center Contact	Gold plated brass
Bend Radius	30.50mm
Bend Radius (Rep.)	61.00mm

Customized services: including connectors, length, phase matching/tracking, time delay, and better electrical performance.

RCT500/RCP760 Structure Characteristics



Structure	Material	ΦD(mm)
1.Center Conductor	Single-core Silver-plated Copper	1.02
2.Dielectric	LD-PTFE	3.07
3.Inner shield	Silver-plated Copper Tape Braiding	3.27
4.Interlayer	LD-PTFE	3.57
5.Outer Shield	Silver-plated Copper Wire Braiding	3.97
6.Jacket	Yellow FEP	4.60
7.Spring	Stainless steel Tape	6.40
8.Braided Layer	Tinned Wire	6.90
9.Stable Layer	PTFE	7.15
10.Armor Jacket	Purplish Black PTFE	7.60

Product Selection and Loss Index @25°C

RFTOP P/N	3GHz	10GHz	18GHz
RCP760H-NMNM-600	0.74 dB	1.06 dB	1.29 dB
RCP760H-NMNM-1M	0.96 dB	1.50 dB	1.88 dB
RCP760H-NMNM-1.5M	1.25 dB	2.05 dB	2.62 dB
RCP760H-NMNM-2M	1.53 dB	2.60 dB	3.35 dB