


L-Shape Rigid Coaxial Cable Assembly, RCS086L-KMKF-L1-L2

2.92mm Male to 2.92mm Female, DC-40GHz, ø2.2mm

Dimensions(mm) Tolerance $\pm 1\%$



Electrical & Environmental

Frequency Range	DC-40GHz, 50 Ohms
Avg Power@25°C	20.3W @40GHz
I L@1M	dB Max @40GHz
VSWR	Max
Capacitance	87 pF/m
VOP	81%
SE	110dB Min
Voltage	1000V@DC
Temp. Phase	750 PPM Max
OT	-55~+125°C

RCS086L Structure Characteristics



Structure	Material	ΦD(mm)
1.Center Conductor	Single-core Silver-plated Copper	0.51
2.Dielectric	LD-PTFE	1.43
3.Outer Shield	Tin-plated Seamless Copper Tube	2.20

Product Selection and Loss Index @25°C

RFTOP P/N	3GHz	22GHz	40GHz
-----------	------	-------	-------

Product Information

Product Number	RCS086L-KMKF-L1-L2
Product Type	Rigid Coaxial Cable Assembly
Cable	RCS086L
Connector	2.92mm(K,SK) Male to 2.92mm(K,SK) Female
Connector Body	Passivated stainless steel
Center Contact	Gold plated beryllium copper
Bend Radius	8.50mm
Bend Radius (Rep.)	N/A

Customized services: including connectors, length, phase matching/tracking, time delay, and better electrical performance.



Microwave and Millimeter wave products
supplier

RFTOP® Technology Co., Ltd.
www.rftop.com service@rftop.com 86-755-88840350