


SMA Female Airline Bulkhead Connector, RC27SF-AF4D13-XX DC-26.5GHz, Straight, 4 hole flange, 8mm×5mm Hole Spacing

Dimensions(mm) Tolerance±1%



Product Selection

D(mm)	L(mm)	RFTOP P/N
0.30	2.00	RC27SF-AF4D13-0301
0.50	6.00	RC27SF-AF4D13-0501
0.60	26.00	RC27SF-AF4D13-0601
0.64	2.50	RC27SF-AF4D13-06401
0.64	6.00	RC27SF-AF4D13-06402
0.64	20.80	RC27SF-AF4D13-06403
0.64	18.00	RC27SF-AF4D13-06404
0.80	21.30	RC27SF-AF4D13-0801
0.80	24.90	RC27SF-AF4D13-0802
0.80	60.00	RC27SF-AF4D13-0803

Electrical & Environmental

Frequency Range	DC-26.5GHz	Impedance	50 ohm
VSWR	1.2 max	Withstand Voltage	1000 V
Insulation Resistance	≥ 5000 MΩ	Contact Resistance	≤ In:3.0/Out:2.0 mΩ
Mating Cycles	> 500 Cycles	Temperature Range	-55℃~+165℃

Mechanical & Product Information

Product Number	RC27SF-AF4D13-XX	Connector	SMA Female
Shape/Mounting	Straight , 4 hole flange	Attachment Method	Solder
Connector Body	Passivated stainless steel	Insulator	PTFE&PEI
Center Contact	Gold plated beryllium copper		