


SMA母头2孔法兰介质穿墙连接器, RC27SF-PF2D04-XX DC-26.5GHz, 安装孔距12.2mm

结构尺寸图 (单位: mm) 误差±1%



产品规格选型表

D1(mm)	L1(mm)	D2(mm)	L2(mm)	RFTOP P/N
0.30	1.27	2.20	3.00	RC27SF-PF2D04-0301
0.30	1.27	2.20	3.20	RC27SF-PF2D04-0302
0.30	1.30	2.20	4.30	RC27SF-PF2D04-0303
0.64	3.00	2.10	6.50	RC27SF-PF2D04-06401
0.64	3.00	2.10	10.00	RC27SF-PF2D04-06402
0.64	3.00	2.10	15.00	RC27SF-PF2D04-06403
0.64	3.00	3.90	15.00	RC27SF-PF2D04-06404

电气与环境性能

频率范围	DC-26.5GHz	特性阻抗	50 ohm
电压驻波比	1.2 max	介质耐压	1000 V
绝缘电阻	≥ 5000 MΩ	接触电阻	≤ In:3.0/Out:2.0 mΩ
耐久性	> 500 次	工作温度	-55°C~+165°C

产品和材料信息

产品型号	RC27SF-PF2D04-XX	接头类型	SMA 母头
外形结构	Straight , 2 hole flange	安装方式	Solder
连接器主体	Passivated stainless steel	绝缘支撑	PTFE&PEI
内导体	Gold plated beryllium copper		



微信扫描
关注我们

RFTOP®频优微波
高品质微波毫米波器件供应商

www.rftop.cn
service@rftop.com 0755-88840350

微信扫描
在线咨询






SMA母头2孔法兰介质穿墙连接器, RC27SF-PF2D04-XX

DC-26.5GHz, 安装孔距12.2mm

典型测试数据



微信扫描
关注我们

RFTOP®频优微波
高品质微波毫米波器件供应商

www.rftop.cn
service@rftop.com 0755-88840350

微信扫描
在线咨询

