


2.92mm Female Bulkhead Flange Connector, RC40KF-MF4D13-XX DC-40GHz, Straight, 4 hole flange, 8mm×5mm Hole Spacing

Dimensions(mm) Tolerance±1%



Product Selection

D1(mm)	L1(mm)	D2(mm)	L2(mm)	RFTOP P/N
0.20	1.50	4.00	3.00	RC40KF-MF4D13-0201
0.30	1.50	4.00	1.40	RC40KF-MF4D13-0301
0.30	1.50	4.00	3.00	RC40KF-MF4D13-0302
0.30	5.00	4.00	3.00	RC40KF-MF4D13-0303
0.30	1.50	4.00	3.20	RC40KF-MF4D13-0304
0.30	1.00	4.00	4.00	RC40KF-MF4D13-0305
0.30	0.50	4.00	10.10	RC40KF-MF4D13-0306
0.38	2.00	4.00	3.00	RC40KF-MF4D13-0381
0.60	1.27	4.00	4.00	RC40KF-MF4D13-0601
0.60	1.27	4.00	10.10	RC40KF-MF4D13-0602

Electrical & Environmental

Frequency Range	DC-40GHz	Impedance	50 ohm
VSWR	1.2 max	Withstand Voltage	750 V
Insulation Resistance	≥ 5000 MΩ	Contact Resistance	≤ In:3.0/Out:2.0 mΩ
Mating Cycles	> 500 Cycles	Temperature Range	-55℃~+165℃

Mechanical & Product Information

Product Number	RC40KF-MF4D13-XX	Connector	2.92mm(K,SK) Female
Shape/Mounting	Straight , 4 hole flange	Attachment Method	Solder
Connector Body	Passivated stainless steel	Insulator	PEI or PEI&PTFE
Center Contact	Gold plated beryllium copper		