


## SMA 2 Way Microstrip Power Divider, RPD003F8S2 30MHz-8GHz, 20W , P-Grade

### Dimensions(mm) Tolerance $\pm 1\%$



### Electrical & Environmental

<b>Frequency Range</b>	30MHz-8GHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.25 max (250-8000M) ; 2.0max (30-250M)		
<b>Output Port VSWR</b>	1.2 max (80-8000M) ; 1.7max (30-80M)		
<b>Insertion Loss</b>	2.8dB max (Excluding theoretical loss未含理论损耗3.0dB)		
<b>Isolation</b>	20dB min (180-8000M) ; 5dB (30-180M)		
<b>Amplitude Balance</b>	$\pm 0.3$ dB		
<b>Phase Balance</b>	$\pm 3^\circ$		
<b>Input Avg Power</b>	20 Watts max @25°C (Derate linearly to 2 Watt at 100°C) (Combiner合路器用时2W)		
<b>Operating Temp</b>	-45°C ~ +85°C		

### Mechanical & Product Information

<b>Product Number</b>	RPD003F8S2, P-Grade	<b>Way</b>	2
<b>Connector</b>	SMA Female	<b>Connector Body</b>	Passivated stainless steel
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Black paint		
<b>Dimensions</b>	150×28×10mm	<b>Net Weight</b>	About 130.0g