


## N 2 Way Microstrip Power Divider, RPD01F1N2W100 100-1000MHz, 100W

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	100-1000MHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.4 max (Typ.1.18)		
<b>Output Port VSWR</b>	1.2 max (Typ.1.14)		
<b>Insertion Loss</b>	0.6dB max Max. 0.8dB (Excluding theoretical loss未含理论损耗3.0dB)		
<b>Isolation</b>	20dB min (120M-1000M) ; 18dB (100M-120M)		
<b>Amplitude Balance</b>	± 0.2dB		
<b>Phase Balance</b>	±2°		
<b>Input Avg Power</b>	100 Watts max @25°C (Derate linearly to 10 Watt at 100°C) (Combiner合路器用时10W)		
<b>Operating Temp</b>	-35°C ~ +75°C		

### Mechanical & Product Information

<b>Product Number</b>	RPD01F1N2W100	<b>Way</b>	2
<b>Connector</b>	N Female	<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Sandblasting natural color conductive oxide		
<b>Dimensions</b>	290×74×20mm	<b>Net Weight</b>	-