


## N 2 Way Microstrip Power Divider, RPD01F2N2 100-2000MHz, 30W , P-Grade

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	100-2000MHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.25 max		
<b>Output Port VSWR</b>	1.2 max		
<b>Insertion Loss</b>	1.8dB max (Excluding theoretical loss未含理论损耗3.0dB)		
<b>Isolation</b>	20dB min (Typ.26dB)		
<b>Amplitude Balance</b>	± 0.3dB		
<b>Phase Balance</b>	±3°		
<b>Input Avg Power</b>	30 Watts max @25°C (Derate linearly to 3 Watt at 100°C) (Combiner合路器用时2W)		
<b>Operating Temp</b>	-35°C ~ +75°C		

### Mechanical & Product Information

<b>Product Number</b>	RPD01F2N2, P-Grade	<b>Way</b>	2
<b>Connector</b>	N Female	<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Black paint		
<b>Dimensions</b>	110×62×20mm	<b>Net Weight</b>	About 290.0g