


## SMA 4 Way Microstrip Power Divider, RPD04F8S4

### 0.4-8GHz, 30W , P-Grade

#### Dimensions(mm) Tolerance±1%



#### Electrical & Environmental

<b>Frequency Range</b>	0.4-8GHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.3 max (Typ.1.18)		
<b>Output Port VSWR</b>	1.2 max (Typ.1.12)		
<b>Insertion Loss</b>	2dB max (Excluding theoretical loss未含理论损耗6.0dB)		
<b>Isolation</b>	18dB min (Typ.26dB)		
<b>Amplitude Balance</b>	± 0.4dB		
<b>Phase Balance</b>	±4°		
<b>Input Avg Power</b>	30 Watts max @25°C (Derate linearly to 3 Watt at 100°C) (Combiner合路器用时1W)		
<b>Operating Temp</b>	-40°C ~ +75°C		

#### Mechanical & Product Information

<b>Product Number</b>	RPD04F8S4, P-Grade	<b>Way</b>	4
<b>Connector</b>	SMA Female	<b>Connector Body</b>	Passivated stainless steel
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Black paint		
<b>Dimensions</b>	110×58×10mm	<b>Net Weight</b>	About 160.0g