


## SMA 8 Way Microstrip Power Divider, RPD1F12S8 1-12GHz, 20W , P-Grade

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	1-12GHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.6 max (Typ.1.24)		
<b>Output Port VSWR</b>	1.3 max (Typ.1.16)		
<b>Insertion Loss</b>	3.2dB max (Excluding theoretical loss未含理论损耗9.0dB)		
<b>Isolation</b>	18dB min (Typ.24dB)		
<b>Amplitude Balance</b>	± 0.4dB		
<b>Phase Balance</b>	±6°		
<b>Input Avg Power</b>	20 Watts max @25°C (Derate linearly to 2 Watt at 100°C) (Combiner合路器用时1W)		
<b>Operating Temp</b>	-45°C ~ +85°C		

### Mechanical & Product Information

<b>Product Number</b>	RPD1F12S8, P-Grade	<b>Way</b>	8
<b>Connector</b>	SMA Female	<b>Connector Body</b>	Passivated stainless steel
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Black paint		
<b>Dimensions</b>	110×106×10mm	<b>Net Weight</b>	About 320.0g