


## SMA 3 Way Resistive Power Divider, RPD3S3-1 DC-3GHz, 2W

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	DC-3GHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.25 max (Typ.1.14)		
<b>Output Port VSWR</b>	1.25 max (Typ.1.14)		
<b>Insertion Loss</b>	10dB max		
<b>Isolation</b>	8.9dB min		
<b>Amplitude Balance</b>	± 0.6dB		
<b>Input Avg Power</b>	2 Watts max @25°C (Derate linearly to 0.2 Watt at 100°C)		
<b>Operating Temp</b>	-35°C ~ +75°C		

### Mechanical & Product Information

<b>Product Number</b>	RPD3S3-1	<b>Way</b>	3
<b>Connector</b>	SMA Female	<b>Connector Body</b>	Passivated stainless steel
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Black paint		
<b>Dimensions</b>	25.4×29.3×16mm	<b>Net Weight</b>	About 33.0g

## SMA 3 Way Resistive Power Divider, RPD3S3-1 DC-3GHz, 2W

### Typical Test Data

