


## TNC 2 Way Microstrip Power Divider, RPDE08F205T2 800-2500MHz, 20W , E-Grade , DC Block

### Dimensions(mm) Tolerance±1%



### Electrical & Environmental

<b>Frequency Range</b>	800-2500MHz	<b>Impedance</b>	50 Ohm
<b>Input Port VSWR</b>	1.25 max (Typ.1.16)		
<b>Output Port VSWR</b>	1.2 max (Typ.1.12)		
<b>Insertion Loss</b>	0.6dB max (Excluding theoretical loss未含理论损耗3.0dB)		
<b>Isolation</b>	20dB min (Typ.26dB)		
<b>Amplitude Balance</b>	$\pm 0.2$ dB		
<b>Phase Balance</b>	$\pm 3^\circ$		
<b>Input Avg Power</b>	20 Watts max @25°C (Derate linearly to 2 Watt at 100°C) (Combiner合路器用时2W)		
<b>Power Supply</b>	24V		
<b>Operating Temp</b>	-35°C ~ +75°C		

### Mechanical & Product Information

<b>Product Number</b>	RPDE08F205T2, E-Grade, DC Block	<b>Way</b>	2
<b>Connector</b>	TNC Female	<b>Connector Body</b>	Ternary alloy plated brass
<b>Center Contact</b>	Gold plated beryllium copper		
<b>Housing</b>	Sandblasting natural color conductive oxide		
<b>Dimensions</b>	50.8×50.8×21mm	<b>Net Weight</b>	About 140.0g