

WR2100(R4) Waveguide Calibration Kits, RWCK2100N 0.35-0.53GHz, N Female, UDR4 Flange

Dimensions(mm) Tolerance \pm 1%

Electrical & Environmental

| | |
|-------------------|--------------|
| Frequency Range | 0.35-0.53GHz |
| Temperature Range | -40°C~+85°C |

Mechanical & Product Information

| | |
|----------------|---|
| Product Number | RWCK2100N |
| Product Type | Waveguide Calibration Kits |
| Connector | N Female |
| Waveguide 1 | WR2100(R4), UDR4 Flange |
| Waveguide Body | Aluminum, grey painted |
| Center Contact | Aluminum, electric conductive oxidation |

RWCK2100N List of Calibration Kit

| Product Name | RFTOP P/N | VSWR | Qty |
|--------------|-----------|----------|-----|
| 波导同轴转换器 | RWR2100N | 1.2 Max | 2 |
| 匹配负载 | RWT2100 | 1.03 Max | 1 |
| 1/4波定长块 | RWGQL2100 | - | 1 |
| 短路块 | RWGSC2100 | - | 1 |
| 配套紧固螺丝 | M12 | - | 90 |
| 包装箱 | 定制款 | - | 1 |

Notes

- 1、Click on the list model to view the specification sheet for the model product.