




## WR284(R32) Waveguide Calibration Kits, RWCK284S 2.6-3.95GHz, SMA Female, UDR32 Flange

Dimensions(mm) Tolerance $\pm$ 1%



### Electrical & Environmental

|                   |             |
|-------------------|-------------|
| Frequency Range   | 2.6-3.95GHz |
| Temperature Range | -40°C~+85°C |

### Mechanical & Product Information

|                |   |
|----------------|---|
| Product Number | RWCK284S                                |
| Product Type   | Waveguide Calibration Kits              |
| Connector      | SMA Female                              |
| Waveguide 1    | WR284(R32), UDR32 Flange                |
| Waveguide Body | Aluminum, grey painted                  |
| Center Contact | Aluminum, electric conductive oxidation |

### RWCK284S List of Calibration Kit

| Product Name | RFTOP P/N | VSWR     | Qty |
|--------------|-----------|----------|-----|
| 波导同轴转换器      | RWR284S   | 1.2 Max  | 2   |
| 匹配负载         | RWT284    | 1.03 Max | 1   |
| 1/4波定长块      | RWGQL284  | -        | 2   |
| 短路块          | RWGSC284  | -        | 2   |
| 配套紧固螺丝       | M6-30     | -        | 30  |
| 包装箱          | 定制款       | -        | 1   |

### Notes

- Click on the list model to view the specification sheet for the model product.