

## WR650(R14) Waveguide Calibration Kits, RWCK650N 1.13-1.73GHz, N Female, UDR14 Flange

Dimensions(mm) Tolerance $\pm$ 1%

### Electrical & Environmental

|                   |              |
|-------------------|--------------|
| Frequency Range   | 1.13-1.73GHz |
| Temperature Range | -40°C~+85°C  |

### Mechanical & Product Information

|                |   |
|----------------|---|
| Product Number | RWCK650N                                |
| Product Type   | Waveguide Calibration Kits              |
| Connector      | N Female                                |
| Waveguide 1    | WR650(R14), UDR14 Flange                |
| Waveguide Body | Aluminum, grey painted                  |
| Center Contact | Aluminum, electric conductive oxidation |

### RWCK650N List of Calibration Kit

| Product Name | RFTOP P/N | VSWR     | Qty |
|--------------|-----------|----------|-----|
| 波导同轴转换器      | RWR650N   | 1.2 Max  | 2   |
| 匹配负载         | RWT650    | 1.03 Max | 1   |
| 1/4波定长块      | RWGQL650  | -        | 1   |
| 短路块          | RWGSC650  | -        | 1   |
| 配套紧固螺丝       | M8-40     | -        | 30  |
| 包装箱          | 定制款       | -        | 1   |

#### Notes

- 1、Click on the list model to view the specification sheet for the model product.