

WRD200 Waveguide Calibration Kits, **RWDCK200N** 2-6GHz, N Female, FPWRD200 Flange

Dimensions(mm) Tolerance \pm 1%

Electrical & Environmental

| | |
|-------------------|-------------|
| Frequency Range | 2-6GHz |
| Temperature Range | -40°C~+85°C |

Mechanical & Product Information

| | |
|----------------|---|
| Product Number | RWDCK200N |
| Product Type | Waveguide Calibration Kits |
| Connector | N Female |
| Waveguide 1 | WRD200, FPWRD200 Flange |
| Waveguide Body | Aluminum, grey painted |
| Center Contact | Aluminum, electric conductive oxidation |

RWDCK200N List of Calibration Kit

| Product Name | RFTOP P/N | VSWR | Qty |
|--------------|-----------|---------|-----|
| 波导同轴转换器 | RWRD200N | 1.3 Max | 2 |
| 匹配负载 | RWDT200 | - | 1 |
| 1/4波定长块 | RWDGQL200 | - | 1 |
| 短路块 | RWDGSC200 | - | 1 |
| 配套紧固螺丝 | M3-30 | - | 24 |
| 包装箱 | 定制款 | - | 1 |

Notes

- 1、Click on the list model to view the specification sheet for the model product.